

SB 2-URTK/SP - Bridge bar

0360012

<https://www.phoenixcontact.com/ie/products/0360012>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Bridge bar, pitch: 8.2 mm, number of positions: 2, color: silver-colored



SB 2-URTK/SP - Bridge bar



0360012

<https://www.phoenixcontact.com/ie/products/0360012>

Technical data

Product properties

| | |
|---------------------|--------|
| Number of positions | 2 |
| Pitch | 8.2 mm |
| Potentials | 1 |

Connection data

| | |
|-------------------|----------------|
| Tightening torque | 1.2 ... 1.5 Nm |
|-------------------|----------------|

Dimensions

| | |
|-------|--------|
| Pitch | 8.2 mm |
|-------|--------|

Material specifications

| | |
|----------|----------------|
| Color | silver-colored |
| Material | Copper |

Environmental and real-life conditions

Ambient conditions

| | |
|--|--|
| Ambient temperature (operation) | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 90 % |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Mounting

| | |
|---------------|----------------|
| Mounting type | Screw mounting |
|---------------|----------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact (Ireland) Ltd
C6 The Exchange, Calmount Park, Ballymount
Dublin 12, D12 XE18
+353/1/2051-300
info@phoenixcontact.ie