

# Product datasheet

Specifications



## Kaedra - for modular device - 2 x 12 modules - 2 terminal blocks

Local distributor code:

402638708

13433

**EAN Code: 3303430134336**

### Main

Range	Mureva
Product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
enclosure type	Enclosure for modular device
Mounting plate description	Without mounting plate

### Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	24
Number of horizontal rows	2
Electrical insulation class	Double insulation Class II
Provided equipment	2 marking kit 2 wiring strap 1 terminal block support 2 terminal block 22 holes
Type of front cover	Transparent Reversible
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	2 earth / neutral (screw connection) with 22 outgoing
Distribution block outgoing	22 x 10 mm <sup>2</sup> 22 x 16 mm <sup>2</sup>
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	460 mm
Depth	160 mm
Internal depth	88 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

<b>Standards</b>	IEC 60670-1 IEC 60670-24 EN 50262 IEC 60695-2-1
<b>Fire resistance</b>	650 °C conforming to IEC 60695-2-1
<b>IP degree of protection</b>	IP65 conforming to IEC 60529
<b>IK degree of protection</b>	IK09 conforming to EN 50102
<b>Environmental characteristics (UV)</b>	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
<b>Overvoltage category</b>	II
<b>Ambient air temperature for operation</b>	-25...60 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	17.000 cm
<b>Package 1 Width</b>	35.500 cm
<b>Package 1 Length</b>	47.200 cm
<b>Package 1 Weight</b>	3.578 kg
<b>Unit Type of Package 2</b>	X12
<b>Number of Units in Package 2</b>	28
<b>Package 2 Height</b>	110.000 cm
<b>Package 2 Width</b>	80.000 cm
<b>Package 2 Length</b>	120.000 cm
<b>Package 2 Weight</b>	112.184 kg

## Logistical informations

<b>Country of origin</b>	IT
--------------------------	----

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	21 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	17 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Average percentage of recycled plastic content	26 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5305d5d6-3783-4b3d-abd0-61fa4a6023d7
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
Halogen-free status	Halogen free plastic parts product
PVC free	Yes

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	86
End of life manual availability	No need of specific recycling operations
Take-back	No

Technical Illustration

Exploded view

---

