

Product datasheet

Specifications



mini Kaedra - for modular device - 1 openings - 8 modules - 4 terminal blocks

Local distributor code:

385332037

13443

EAN Code: 3303430134435

Main

| | |
|----------------------------|-----------------------------------|
| Range | Mureva |
| Product name | Mureva Enclosure |
| Product or component type | Weatherproof enclosure |
| enclosure type | Mini enclosure for modular device |
| Mounting plate description | Without mounting plate |

Complementary

| | |
|---------------------------------|---|
| Enclosure mounting | Surface |
| 9 mm pitches | 16 |
| Number of 18 mm modules per row | 8 |
| Total number of 18 mm modules | 8 |
| Number of horizontal rows | 1 |
| Electrical insulation class | Class II Double insulation |
| Provided equipment | 1 marking kit 4 terminal block 4 holes |
| Type of front cover | Transparent |
| Power dissipation in W | 15 W |
| [In] rated current | 63 A |
| Type of rail | DIN |
| Number of pre-cutouts PG ISO | 5 |
| Number of terminal blocks | 4 earth / neutral (screw connection) with 4 outgoing |
| Distribution block outgoing | 8 x 10 mm ² 8 x 16 mm ² |
| Locking options description | Optional keylock |
| Enclosure material | Self-extinguishing polymer |
| Width | 195 mm |
| Height | 200 mm |
| Depth | 112 mm |
| Internal depth | 56 mm |
| Colour | Door: transparent green Enclosure: light grey (RAL 7035) |

Environment

| | |
|--|---|
| Standards | IEC 60670-1 IEC 60670-24 EN 50262 IEC 60695-2-1 |
| Fire resistance | 650 °C conforming to IEC 60695-2-1 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to EN 50102 |
| Environmental characteristics (UV) | UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage category | II |
| Ambient air temperature for operation | -25...60 °C |

Packing Units

| | |
|-------------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.000 cm |
| Package 1 Width | 24.500 cm |
| Package 1 Length | 26.000 cm |
| Package 1 Weight | 750.000 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 22.000 cm |
| Package 2 Width | 34.500 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 4.880 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 144 |
| Package 3 Height | 80.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 122.000 kg |

Logistical informations

| | |
|--------------------------|----|
| Country of origin | IT |
|--------------------------|----|

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 5 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 4 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.1 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.1 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.8 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|--|
| Average percentage of recycled plastic content | 25 % |
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | 5305d5d6-3783-4b3d-abd0-61fa4a6023d7 |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |
| Halogen-free status | Halogen free plastic parts product |
| PVC free | Yes |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------------------|--|
| Recyclability potential, in % | 86 |
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |