

Specifications



Photo is representative



Eaton 174513

Eaton Moeller series xEffect - AZ MCB.
Miniature circuit breaker (MCB), 100A, 3p,
type B characteristic

General specifications

PRODUCT NAME	Eaton Moeller series xEffect - AZ MCB
CATALOG NUMBER	174513
EAN	4015081709694
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	81 mm
PRODUCT WEIGHT	0.699 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	EN45545-2 IEC 61373
MODEL CODE	AZ-3-B100



Powering Business Worldwide

Additional information

CURRENT LIMITING CLASS

3

FEATURES

Additional equipment possible

SPECIAL FEATURES

Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity

USED WITHAZ
Miniature circuit breaker

Delivery programme

AMPERAGE RATING

100 A

APPLICATION

- Switchgear for industrial and advanced commercial applications
- xEffect - Switchgear for industrial and advanced commercial applications

NUMBER OF POLES

Three-pole

NUMBER OF POLES (PROTECTED)

3

NUMBER OF POLES (TOTAL)

3

RELEASE CHARACTERISTIC

B

TRIPPING CHARACTERISTIC

B

TYPE

- AZ
- Miniature circuit breaker

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	27.3 W
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	9.1 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	100 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	2
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
RATED INSULATION VOLTAGE (UI)	440 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	400 V
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 230 V	20 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 400 V	20 kA
RATED SWITCHING CAPACITY (IEC/EN 60947-2)	20 kA
VOLTAGE TYPE	AC

Technical data - mechanical

BUILT-IN DEPTH	75 mm
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX	50 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN	2.5 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX	50 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN	2.5 mm ²
DEGREE OF PROTECTION	IP20
WIDTH IN NUMBER OF MODULAR SPACINGS	4.5

Resources

APPLICATION NOTES	eaton-maximum-cable-lengths-for-eatons-protective-devices-brochure-br034006en-en-us.pdf eaton-quality-standards-for-railway-applications-application-paper-ap003005en-en-us.pdf
BROCHURES	eaton-pdd-railrolling-stock-brochure-br011002en-en-us.pdf
CHARACTERISTIC CURVE	eaton-xeffect-az-mcb-characteristic-curve.jpg eaton-xeffect-az-mcb-characteristic-curve-003.jpg
DECLARATIONS OF CONFORMITY	eaton-mcb-declaration-of-conformity-eu250431en.pdf
DRAWINGS	eaton-xpole-mmct-mcb-dimensions.jpg eaton-xeffect-az-mcb-3d-drawing-002.jpg eaton-xeffect-az-mcb-3d-drawing.jpg
ECAD MODEL	ETN.AZ-3-B100.edz
INSTALLATION INSTRUCTIONS	IL019148ZU
MCAD MODEL	eaton-non-selective-universal-mcb-mcad-3d-models-az-plht-3p.stp
PEP ECO-PASSPORT	eaton-non-selective-universal-mcb-pep-eato-00259-v0101-en.pdf
WIRING DIAGRAMS	eaton-xpole-mmc4-6-m-mcb-wiring-diagram-005.jpg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

