

# Specifications

## Eaton 235448

Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB. Residual current circuit breaker (RCCB), 80A, 4p, 300mA, type A, MW

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller series xPole - PFIM Type AC, A, U, R RCCB
<b>CATALOG NUMBER</b>	235448
<b>EAN</b>	4015082354480
<b>PRODUCT LENGTH/DEPTH</b>	76 mm
<b>PRODUCT HEIGHT</b>	80 mm
<b>PRODUCT WIDTH</b>	70 mm
<b>PRODUCT WEIGHT</b>	0.384 kg
<b>COMPLIANCES</b>	RoHS conform
<b>CERTIFICATIONS</b>	IEC/EN 61008
<b>MODEL CODE</b>	PFIM-80/4/03-A-MW



Powering Business Worldwide

## Additional information

**ACCESSORIES REQUIRED** Z-HK 248432

**FEATURES** Residual current circuit breaker  
Additional equipment possible

**FITTED WITH:** Interlocking device

**SPECIAL FEATURES**

- Maximum operating temperature is 60 °C: Starting at 40 °C, the max. permissible continuous current decreases by 1.2% for every 1 °C
- Tripping signal contact for subsequent installation Z-NHK 248434

**USED WITH** Residual current circuit breakers  
PFIM  
Type A  
KLV-TC-4 276241 (Compact enclosure)  
Z-FW/LP 248296 (Remote control and automatic switching device)  
Z-RC/AK-4MU 101062 (sealing cover set)

## Delivery programme

**AMPERAGE RATING** 80 A

**APPLICATION**

- Residual current circuit breaker for residential and commercial applications
- xPole - Switchgear for residential and commercial applications

**FAULT CURRENT RATING** 300 mA

**IMPULSE WITHSTAND CURRENT** Partly surge-proof 250 A

**NUMBER OF POLES** Four-pole

**RATED SHORT-CIRCUIT STRENGTH** 10 kA

**SENSITIVITY TYPE** Pulse-current sensitive

**TRIPPING TIME** Non-delayed

**TYPE**

- PFIM
- Residual current circuit breakers
- Type A

## Design verification to IEC/EN 61439

<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION</b>	Does not apply, since the

## Design verification to IEC/EN 61439 - technical data

<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>	11.4 W
<b>HEAT DISSIPATION CAPACITY</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT</b>	0 W
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	80 A
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT</b>	0 W

<b>AGAINST ELECTRIC SHOCK</b>	entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.

### Technical data - electrical

<b>ADMISSIBLE BACK-UP FUSE OVERLOAD - MAX</b>	50 A gG/gL
<b>FREQUENCY RATING</b>	50 Hz
<b>LEAKAGE CURRENT TYPE</b>	A
<b>LIFESPAN, ELECTRICAL</b>	4000 operations
<b>POLLUTION DEGREE</b>	2
<b>RATED FAULT CURRENT - MAX</b>	0.3 A
<b>RATED FAULT CURRENT - MIN</b>	0.3 A
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4 kV
<b>RATED INSULATION VOLTAGE (UI)</b>	440 V
<b>RATED OPERATIONAL VOLTAGE (UE) - MAX</b>	400 V
<b>RATED RESIDUAL MAKING AND BREAKING CAPACITY</b>	800 A
<b>RATED SHORT-TIME WITHSTAND CURRENT (ICW)</b>	10 kA
<b>SHORT-CIRCUIT RATING</b>	80 A (max. admissible back-up fuse)
<b>SURGE CURRENT CAPACITY</b>	0.25 kA
<b>TEST CIRCUIT RANGE</b>	196 V AC - 456 V AC
<b>VOLTAGE RATING</b>	230 V AC / 400 V AC

### Technical data - mechanical

<b>BUILT-IN DEPTH</b>	70.5 mm
<b>BUILT-IN WIDTH (NUMBER OF UNITS)</b>	70 mm (4 SU)
<b>BUSBAR MATERIAL THICKNESS</b>	0.8 mm - 2 mm
<b>CLIMATIC PROOFING</b>	25-55 °C / 90-95% relative humidity according to IEC 60068-2
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX</b>	16 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN</b>	1.5 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX</b>	35 mm <sup>2</sup>
<b>CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN</b>	1.5 mm <sup>2</sup>
<b>DEGREE OF PROTECTION</b>	IP20 IP20, IP40 with suitable enclosure
<b>FRAME</b>	45 mm
<b>LIFESPAN, MECHANICAL</b>	20000 operations
<b>MOUNTING METHOD</b>	Quick attachment with 2 latch positions for DIN-rail

	IEC/EN 60715 DIN rail
<b>PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MAX</b>	60 °C
<b>PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MIN</b>	-35 °C
<b>TERMINAL CAPACITY (SOLID WIRE)</b>	1.5 mm <sup>2</sup> - 35 mm <sup>2</sup>
<b>TERMINAL CAPACITY (STRANDED CABLE)</b>	16 mm <sup>2</sup> (2x)
<b>TERMINAL PROTECTION</b>	Finger and hand touch safe, DGUV VS3, EN 50274
<b>TERMINALS (TOP AND BOTTOM)</b>	Open mouthed/lift terminals
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	4

## Resources

APPLICATION NOTES	<a href="#">eaton-rcd-application-guide-br019003en-en-us.pdf</a>
CATALOGUES	<a href="#">eaton-xpole-protective-devices-catalog-ca019014en-en-us.pdf</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-rccb-declaration-of-conformity-uk251421en.pdf</a> <a href="#">eaton-rccb-declaration-of-conformity-eu250135en.pdf</a>
ECAD MODEL	<a href="#">ETN.PFIM-80_4_03-A-MW.edz</a>
INSTALLATION INSTRUCTIONS	<a href="#">IL019172ZU</a> <a href="#">eaton-mcb-rccb-rcbo-g9-il019140zu.pdf</a>
MCAD MODEL	<a href="#">eaton-rccb-mcad-drawings-pfi-4p.dwg</a> <a href="#">eaton-residual-current-circuit-breakers-3d-models-pfi-4p.stp</a>
PEP ECO-PASSPORT	<a href="#">eaton-residual-current-circuit-breakers-pep-eato-00109-v0101-en.pdf</a>

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

