

Specifications



Photo is representative

Eaton 276288

Main load disconnecter Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240/415 V, 125 A, 3P

General specifications

PRODUCT NAME	Eaton Moeller series IS Disconnecter
CATALOG NUMBER	276288
EAN	4015082762889
PRODUCT LENGTH/DEPTH	60 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	53.1 mm
PRODUCT WEIGHT	0.314 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	EN45545-2 IEC 61373
MODEL CODE	IS-125/3



Powering Business Worldwide

Product specifications

DEGREE OF PROTECTION	IP40 IP10
TERMINALS	Lift terminal
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	16.5 W
IMPRINT/INDICATION	Symbol "arrows"
LAMP SOCKET	Other
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
BUILT-IN DEPTH	69.5 mm
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	6.2 W
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	3
AMPERAGE RATING	125 A
COLOR CALOTTE	Other
SWITCH TYPE	Other
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	2 kA
VOLTAGE TYPE	AC
LAMP TYPE	Other
TYPE	IS. Main load disconnect switch
APPLICATION	Switchgear for industrial and advanced commercial applications
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	3
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	125 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	415 V
RATED SWITCHING CAPACITY	10 kA
STATIC HEAT	0 W

Resources

DECLARATIONS OF CONFORMITY	eaton-disconnector-declaration-of-conformity-eu250428en.pdf
DRAWINGS	eaton-dimensions-mas-is.jpg 1221172
ECAD MODEL	ETN.IS-125_3.edz
MCAD MODEL	eaton-main-load-disconnector-switch-mcad-3d-models-is-3p.stp eaton-main-load-disconnector-switch-mcad-drawings-is-3p.dwg
WIRING DIAGRAMS	IS_3P

DISSIPATION, NON-CURRENT-DEPENDENT

VOLTAGE RATING - MIN 240 V

WIDTH IN NUMBER OF MODULAR SPACINGS 3

NUMBER OF POLES Three-pole

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

