

holder for cylindrical fuses (31113000)



The picture may show a similar product.

Description

Part No.: **31113 000**

AMBUS Panel

holder for cylindrical fuses

10x38 / 3P

32 A / 690 V

for mounting rail

System

Panel

Advantages of the product

large clamping range

holder for label

Product group 17

Subgroup 06

pack size 4

EAN 4021267311131

ECLASS 14.0 27142190
ETIM 5.0 EC002705
ETIM 8.0 EC002705
ETIM 10.0 EC002705

Approvals

Standards

IEC 60947-1:2020
IEC 60947-3:2020 AC ratings only
UL 4248-1

Approvals

IEC (CB) , CSA , UL , CCC



for UL feeder circuits >250V

type number: AES10x38
EAC Type: AES

UL file: E230163, UL category (for USA): IZLT <https://www.ul.com>
UL file: E230163, UL category (for Canada): IZLT7 <https://www.ul.com>
CSA file: 110285, CSA class: 6225-01 <https://directories.csa-international.org>
CCC certificate: 2012010302581751

Technical data

for fuse links size: 10x38
fuse links acc. to standard: IEC / HD 60269-2
permitted power dissipation of the fuse-link: 3 W

Details IEC

Standards

IEC 60947-1:2020
IEC 60947-3:2020 AC ratings only

Electrical data IEC

rated current (IEC): 32 A
rated voltage (IEC) AC: 690 V

rated isolation voltage U_i AC: 800 V
rated surge voltage U_{imp} : 6 kV

Utilisation category AC (IEC 60947-3): AC-22B (400 V)

cond. short-circuit current with fuses (AC): 100 kA / 400 V (32A)
100 kA / 500 V (25A)
approved with fuse links of operation class: gG

power dissipation of the article:
The power dissipation at a typical load of 80 % results to 0,6 W.
(The power dissipation at full load would be 0,9 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

further utilisation category AC (IEC 60947-3): AC-20B (1000 V) at pollution degree 2

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

min. permitted operation temperature -40°C

for fuse links as per IEC / EN 60269-2 with permitted rated power dissipations
up to max. 3W for gG/gL
up to max. 1.2W for aM

Details UL

Standards

UL 4248-1

for UL feeder circuits >250V
suitable for field-installed conductors

Electrical data UL

rated current (UL): 30 A
rated voltage (UL) AC: 600 V
rated frequency (UL): 50 / 60 Hz
rated voltage (UL) DC: 600 V
for wires UL: Cu 75°C

SCCR: 100 kA

Mechanical data

W x H x D: 54 x 81 x 58
weight: 15,5 kg/100
poles: 3-pole
Mounting: for mounting rail

degree of protection: IP20
front degree of protection: IP20

Terminal points

cage clamp connection

| | |
|---------------------|----------------------|
| screw drive: | PZ2 |
| wire stripping: | 11 mm |
| min. cross-section: | 0,75 mm ² |
| max. cross-section: | 25 mm ² |
| Md min.: | 2,0 Nm |
| Md max.: | 2,5 Nm |

Not suitable for aluminium cables !

| | |
|------------------------|---------------|
| min. cross-section UL: | AWG 18 |
| max. cross-section UL: | AWG 4 |
| torque (UL): | 18 - 22 lb-in |
| for wires UL: | Cu 75°C |

or applications acc. to UL / CSA:

for wires AWG 6 - AWG 4: 22 - 26 lb-in

connection of 2 wires (of same cross-section)

for applications acc. to IEC / EN:

Cu 0.75 - 10 mm²

all further details: as for connection of 1 conductor

connection of 2 wires (of same cross-section)

for applications acc. to UL / CSA:

Cu AWG 18 - AWG 6

all further details: as for connection of 1 conductor

Material properties

halogen-free: Yes

Application notes

Not suitable for aluminium cables !

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

permitted power dissipation of the fuse-link: 3 W

for UL feeder circuits >250V

Accessories

connection accessories



31102 000A

comb-type busbar, 3-pole, bridge type, pitch 18 mm
80 A, 1 m long
16 mm²



31103 000

connection terminal, side connection
6 - 25 mm²
for: 31101, 31102



31157 000

connection terminal, front connection
6 - 25 mm²
for: 31101, 31102



31549 000

comb-type busbar, 3-pole, bridge type, pitch 18 mm
100 A, 1 m long
25 mm²



31550 000

connection terminal, front connection
6 - 35 mm²
for: 31549, 31561

<https://pim.woehner.de/EN/FR/1000050839>