

# Specifications



Photo is representative



## Eaton 5E700UI

Eaton 5E Gen2 UPS USB IEC, 700 VA, 360 W,  
Input: C14, Outputs: (4) C13, Tower

### General specifications

<b>PRODUCT NAME</b>	Eaton 5E Gen2 UPS
---------------------	-------------------

<b>CATALOG NUMBER</b>	5E700UI
-----------------------	---------

<b>EAN</b>	3553340704178
------------	---------------

<b>PRODUCT LENGTH/DEPTH</b>	288 mm
-----------------------------	--------

<b>PRODUCT HEIGHT</b>	148 mm
-----------------------	--------

<b>PRODUCT WIDTH</b>	100 mm
----------------------	--------

<b>PRODUCT WEIGHT</b>	4.18 kg
-----------------------	---------

<b>COMPLIANCES</b>	CB LVD Directive EMC Directive RoHS Directive Packaging Directive WEEE Directive Batteries Directive
--------------------	--

<b>CERTIFICATIONS</b>	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC UKCA Cm Ukr IEC/EN 62040-3
-----------------------	--



Powering Business Worldwide

## Product specifications

### SPECIAL FEATURES

- Automatic Voltage Regulation (AVR)
- Saves space with a compact tower design
- HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)

<b>TOPOLOGY</b>	Line-interactive
<b>CONSTRUCTION TYPE</b>	Free standing model
<b>COLOR</b>	Black
<b>VA RATING</b>	700 VA
<b>WATTAGE</b>	360 W
<b>RACK MOUNTING KIT</b>	No
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"><li>• (2) IEC-IEC output cables</li><li>• Quick start</li><li>• Safety instructions</li></ul>
<b>SURGE PROTECTION</b>	Yes
<b>INTERNAL BYPASS</b>	No
<b>HOT SWAP POWER</b>	No
<b>AUTO SHUTDOWN FUNCTION</b>	Yes
<b>PRIMARY FREQUENCY - MAX</b>	63 Hz
<b>PRIMARY FREQUENCY - MIN</b>	45 Hz
<b>INPUT CONNECTION</b>	C14
<b>INPUT NOMINAL VOLTAGE</b>	230V default (220/230/240V)
<b>NOMINAL FREQUENCY</b>	50/60 Hz
<b>INPUT FREQUENCY RANGE</b>	45-63 Hz
<b>RECEPTACLE</b>	(4) C13
<b>NUMBER OF OUTPUTS C13</b>	4
<b>VOLTAGE</b>	230V
<b>OUTPUT NOMINAL VOLTAGE</b>	230V
<b>FEED TYPE</b>	1
<b>VOLTAGE TYPE</b>	AC

## Resources

BROCHURES	<a href="#">eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf</a>
CERTIFICATION REPORTS	<a href="#">eaton-dpq-5egen2-ups-certificate-en-gb.pdf</a>
MANUALS AND USER GUIDES	<a href="#">eaton-dpq-5egen2-ups-manual-en-gb.pdf</a>
TECHNICAL DATA SHEETS	<a href="#">eaton-dpq-5egen2-ups-datasheet-en-gb.pdf</a>

<b>RUNTIME GRAPH</b>	<a href="#">View runtime graph</a>
<b>BATTERY MANAGEMENT</b>	Automatic battery test, deep-discharge protection, cold-start capable
<b>BATTERY RATING</b>	12 V / 7 Ah
<b>BATTERY TYPE</b>	Sealed, lead-acid
<b>EXTENDED BATTERY CAPABILITY</b>	No
<b>COMMUNICATION</b>	USB port (HID compliant)
<b>EXPANSION SLOTS</b>	No
<b>ETHERNET INTERFACE</b>	No
<b>INCLUDES NETWORK CARD</b>	No
<b>SOFTWARE COMPATIBILITY</b>	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
<b>USER INTERFACE</b>	LEDs
<b>TYPE OF INTERFACE</b>	USB
<b>POTENTIAL FREE SWITCH CONTACT</b>	No
<b>RELATIVE HUMIDITY</b>	0-90% non-condensing
<b>TEMPERATURE RANGE</b>	0° to 40°C (32° to 104°F)
<b>OPERATING TEMPERATURE - MAX</b>	40 °C
<b>OPERATING TEMPERATURE - MIN</b>	0 °C
<b>OUTPUT APPARENT POWER</b>	700 VA
<b>INPUT VOLTAGE - MAX</b>	300 V
<b>INPUT VOLTAGE - MIN</b>	140 V
<b>OUTPUT VOLTAGE - MAX</b>	257 V
<b>OUTPUT VOLTAGE - MIN</b>	195 V
<b>SECONDARY FREQUENCY - MAX</b>	60 Hz
<b>SECONDARY FREQUENCY - MIN</b>	50 Hz
<b>BATTERY QUANTITY</b>	1
<b>EFFICIENCY AT MAX. LOAD</b>	95
<b>INPUT VOLTAGE RANGE</b>	140-300 V
<b>OUTPUT FREQUENCY</b>	50/60 Hz
<b>OUTPUT VOLTAGE RANGE</b>	195-257 V
<b>PHASE (INPUT)</b>	1

<b>PHASE (OUTPUT)</b>	1
<b>POWER CONSUMPTION</b>	18.9 W

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

