



EHN111



Daily time switch 1 channel, 3 modules with reserve

Technical characteristics

Architecture

Fixing mode Din-Rail

Functions

Power reserve ≈ 120 h

Configuration

Switch mode change-over contact, usable as NC or NO

Main electrical features

Rated operational voltage U_e 230 / 240 V

Frequency 50/60 Hz

Dimensions

Depth of installed product 60 mm

Height of installed product 90 mm

Width of installed product 54 mm

Power

Power consumed 0.5 VA

Power consumption (operation) 0.5 VA

Total power loss under IN 1 W

Power dissipation per coil 0.5 W

Battery

Charging time of the power reserve in hours 120

Incandescent bulbs control

Max. power with incandescent lamps 900 W

Installation, mounting

Mounting type surface-mounted

Connection

Connection cross-sect. flexible conductor 1 / 4mm²

Connection cross-sect. rigid cable 1 / 4mm²

Type of connection with screw

Number of contacts 1

Type of contacts 1 changeover

Type of connection with screw terminals

Settings

Summer / Winter time change	manual
Shortest switching time	15 mn
Type of programming	analog
Programming cycle	24H
Setting	Setting via day dial

Equipment

Number of channels	1
Supply failure reserve	120 h

Use

Cycle	daily
-------	-------

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-10...55 °C
Working accuracy	5