



### Main

|                                    |                                               |
|------------------------------------|-----------------------------------------------|
| Range                              | Linergy                                       |
| Product name                       | FT                                            |
| Device short name                  | GV2G                                          |
| Product or component type          | Terminal block                                |
| Accessory / separate part category | Connection accessory                          |
| Poles description                  | 3P                                            |
| Range compatibility                | TeSys GV2<br>TeSys Deca<br>TeSys K<br>TeSys U |

### Complementary

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ie] rated operational current | 63 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Mounting location              | 35 mm DIN rail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| IP degree of protection        | IP20 conforming to IEC 60529                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| [Ui] rated insulation voltage  | 690 V conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Connections - terminals        | Screw clamp terminals 1 solid AWG 4<br>Screw clamp terminals 1 cable(s) 1.5...16 mm <sup>2</sup> flexible with cable end<br>Screw clamp terminals 1 cable(s) 1.5...16 mm <sup>2</sup> flexible without cable end<br>Screw clamp terminals 1 cable(s) 1.5...25 mm <sup>2</sup> solid<br>Screw clamp terminals 2 cable(s) 1.5...4 mm <sup>2</sup> flexible with cable end<br>Screw clamp terminals 2 cable(s) 1.5...6 mm <sup>2</sup> solid<br>Screw clamp terminals 2 cable(s) 2.5...4 mm <sup>2</sup> flexible without cable end<br>Screw clamp terminals 1 flexible AWG 4 |
| Tightening torque              | 1.7 N.M - on screw clamp terminals<br>2.2 N.M - on connector                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Net weight                     | 0.115 Kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 5.1 Cm  |
| Package 1 Width              | 11.9 Cm |
| Package 1 Length             | 15.2 Cm |
| Package 1 Weight             | 120.0 G |
| Unit Type of Package 2       | S02     |
| Number of Units in Package 2 | 40      |
| Package 2 Height             | 15.0 Cm |

|                              |          |
|------------------------------|----------|
| Package 2 Width              | 30.0 Cm  |
| Package 2 Length             | 40.0 Cm  |
| Package 2 Weight             | 4.866 Kg |
| Unit Type of Package 3       | P06      |
| Number of Units in Package 3 | 640      |
| Package 3 Height             | 77.0 Cm  |
| Package 3 Width              | 80.0 Cm  |
| Package 3 Length             | 60.0 Cm  |
| Package 3 Weight             | 85.85 Kg |

### Offer Sustainability

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes                                           |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                           |
| Mercury free               | Yes                                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**