essentials™

Technical Specification

Product Code: CL158

Description: Single Isolated Coaxial Outlet

Luckinslive 389086570



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Metal Clad
Colour	Grey
Insert Colour	White
Supplied Fixing Screw Finish	Polished Chrome
Materials	Front Plate & Back Box: Electrophoretically Coated Steel Earth Plate: Mild Steel Insert: Urea Terminals: Brass
Termination Type	Screw
Isolated	Yes
Isolated Comments	Enables 1 way signal, reducing signal interference
Non-Isolated	No
Shielded	No
Supplied Back Box Depth (mm)	40
Back Box Knockouts - Total (mm)	5 x Ø20
Back Box Knockouts - Top (mm)	2 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	None
Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Earth Terminal Supplied	Yes
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN