essentials™

Technical Specification

Product Code: CL1840B

Luckinslive 406093103

Description: 13A 2 Gang Double Pole Safety Shutter Switched Socket Outlet With Outboard Rockers & Neons



General Information

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Metal Clad		
Colour	Grey		
Insert Colour	White		
Supplied Fixing Screw Finish	Polished Chrome		
Materials	Front Plate & Back Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea	
	Rear Housing: Urea	Neon Lens: Polycarbonate	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
3 Pin Safety Shuttered	Yes		
Twin Earth Terminals	Yes		
Neon Indicator	Yes		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	None		
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

The safety shutter will only fully open when all three BS 1363 plug-top pins engage correctly with the shutter. Inserting the earth pin alone will not open the live and neutral shutter like conventional socket shutters.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN