essentials™

Technical Specification

Product Code: CL201

Luckinslive 389086596

Description: 50A 1 Gang Double Pole Plate Switch With Neon



General Information

Dimensions (mm)	80 (W) x 80 (H) x 52 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Metal Clad
Colour	Grey
Insert Colour	White
Supplied Fixing Screw Finish	Polished Chrome
Materials	Front Plate & Back Box: Electrophoretically Coated Steel
	Insert, Switch & Rear Housing: Urea
	Neon Lens: Polycarbonate
	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel
Operating Voltage (AC)	250
Frequency (Hz)	50
Resistive Load Rating (A)	50
Termination Type	Screw
Terminal Size (mm)	Ø6
Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm^2)	1 x 16
Double Pole Switch	Yes
Twin Earth Terminals	Yes
Indicator Colour	Red
Product Marking	On & Off
Supplied Back Box Depth (mm)	50
Back Box Knockouts - Total (mm)	5 x Ø20
Back Box Knockouts - Top (mm)	2 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	None
Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Earth Terminal Supplied	Yes
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN