
GRIDPRO®

Technical Specification

Product Code: CMA20404AG

Description: 4 Gang GridPro® Frontplate

Luckinslive 408391078



General Information

Range	**Part M Range™**
Plate Dimensions (mm)	146 (W) x 86 (H) x 9 (D)
Plate Fixing Centres - Horizontal (mm)	120.6
Style	Part M
Colour	Anthracite Grey
Supplied Fixing Screw Finish	Polished Chrome
Materials	Front Plate: Urea — Fixing Lugs: Brass
Anti Microbial Certified	Yes
Yoke Required	No
Minimum Back Box Depth (mm)	25
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	25

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

STANDARD BACK BOX | NO YOKE | SCREW-IN MODULES

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN