
Part M Range™ Technical Specification

Product Code: CMA2652AG Luckinslive 437662820

Description: 13A Double Pole Switched Lockable Fused Connection Unit With LED





General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Rounded Profile		
Colour	Anthracite Grey		
Supplied Fixing Screw Finish	Polished Chrome		
Materials	Front Plate, Rocker Switch & Fuse Drawer: Urea	Rear Housing: Urea	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel		
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Switched	Yes		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
LED Indicator	Yes	Indicator Colour	Red
Product Marking	Fuse Symbol		
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25		

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN