Part M Range™ Technical Specification

Product Code: CMA401AG

Luckinslive 391934995

Description: 1 Gang MiniGrid® Unfurnished Plate - 1 Aperture





General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
MiniGrid Plate (Gang)	1
MiniGrid Single Width Module Quantity	1
MiniGrid Double Width Module Quantity	0
Style	Rounded Profile
Colour	Anthracite Grey
Supplied Fixing Screw Finish	Polished Chrome
Materials	Front Plate: Urea
Anti Microbial Certified	Yes
Modular Rocker Switches	Yes
Minimum Back Box Depth (mm)	Dependent On Modules Fitted
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	25

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white & grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with modules in the MiniGrid Range. MINIGRID®

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN