Part M Range™ Technical Specification

Product Code: CMA501AG
Description: 50A 1 Gang DP Switch With Neon

Luckinslive 391935143





General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Rounded Profile		
Colour	Anthracite Grey		
Supplied Fixing Screw Finish	Polished Chrome		
Switch Finish	Polar White		
Materials	Front Plate: Urea	Rear Housing: Urea	
	Neon Lens: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	50		
Termination Type	Screw		
Terminal Size (mm)	Ø6	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm²)	1 x 16		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Neon Indicator	Yes	Indicator Colour	Orange
Product Marking	On & Off		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white & grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN