elucian

Technical Specification

Product Code: CU2SPD275T12

Description: 2 Pole 275Uc 40Ka T1 & T2 SPD With Tails



General Information

Dimensions (mm)	36 (W) x 83 (H) x 67 (D)
Colour	Light Grey
Maximum Continuous Operating Voltage (AC) (Uc)	275
SPD Type	Type 1 & 2
Voltage Protection Level (Kv) (Up)	<1.5
Nominal Discharge Current (kA) (In)	12.5 (T1), 20 (T2)
Response Time (ns) (tA)	<25
Compatible Earthing Systems	TT / TN
Visual Indicator Status (Green)	Normal Function
Visual Indicator Status (Red)	Cartridge Replaceable
Device Terminals	Screwed Lug & Pin
SPD Terminal Capacity - L&N (mm^2)	SPD Terminal Torque (Nm) 2
Number Of Poles	2
Ingress Protection	IP20
Operational Temperature (°C)	-40 to +70
Warranty (Years)	3

Standards BS EN 61643-1-11

Additional Information 6mm^2 tails supplied (live, neutral & earth).

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Website Range DoC Installation CLICK OR SCAN