Technical Specification

Product Code: DPBN571UBK Luckinslive 407007266

Description: 13A Ingot 1 Gang Switched Socket Outlet With Single 2.1A USB Outlet





General Information

Dimensions (mm)	91 (W) x 91 (H) x 30 (D)		
Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)		
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Rounded Profile		
Finish	Black Nickel		
Insert Colour	Black		
Gasket Colour	Black		
Supplied Fixing Screw Finish	Black Nickel		
Materials	Front Plate: Stainless Steel	Insert: Urea	
	Housing: Nylon	Switch Cover: Stainless Steel	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	PCB: Mixed Components	Earth Strap: Mild Steel	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
USB Output Type	USB Type 'A'		
USB Number Of Outputs	1	USB Charging Total Load (A)	2.1
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Single Pole Switched	Yes		
Twin Earth Terminals	Yes		
Product Marking	USB 5V 2.1A		
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20	Warranty - Electronics (Years)	2

Standards BS 1363-2: 2016 +A1: 2018, BS EN IEC 62368-1, BS EN 62680-1-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN