Technical Specification

Product Code: DPSC425WH

Luckinslive 404217143

Description: 10AX Ingot 1 Gang Intermediate Plate Switch





General Information

Dimensions (mm)	91 (W) x 91 (H) x 25 (D)
Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
MiniGrid Plate (Gang)	1
MiniGrid Single Width Module Quantity	1
MiniGrid Double Width Module Quantity	0
Style	Rounded Profile
Finish	Satin Chrome
Insert Colour	White
Gasket Colour	White
Supplied Fixing Screw Finish	Polished Chrome
Materials	Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel Insert: Urea Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
Anti Microbial Certified	No
Operating Voltage (AC)	250
Frequency (Hz)	50
Inductive Load Rating (AX)	10
Load Rating Comments	Suitable for Fluorescent or Inductive Loads
Termination Type	Screw
Terminal Size (mm)	Ø3.5
Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm^2)	4 x 1.5 or 2 x 2.5
Modular Rocker Switches	Yes
Intermediate Switch	Yes
Minimum Back Box Depth (mm)	16
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range. MINIGRID®

UK Design Registration: 3015621

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN