essentials™

Technical Specification

Product Code: ES001

Description: 13A 1 Gang Trailing Socket Outlet With Neon

Luckinslive 389119049



General Information

Dimensions (mm)	96 (W) x 62 (D) x 27 (H)		
Materials	Housing: Polycarbonate Internal Busbars: Brass Terminal Screws: Steel and Yellow Passivated	Neon Lens: Polycarbonate Terminals: Brass	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm^2)	1.5		
Number Of Socket Outlets	1		
Switched	No		
Neon Indicator	Yes	Indicator Colour	Red
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation.
Always refer to the circuit diagram supplied with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN