define®

Technical Specification

CLICK® Scolmore GROUP

Product Code: FPBS751WH Luckinslive 389090087

Description: 13A Ingot Double Pole Switched Fused Connection Unit





General Information

Dimensions (mm)	86 (W) x 86 (H) x 26 (D)		
Plate Dimensions (mm)	86 (W) x 86 (H) x 1.3 (D)		
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 3 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Flat Plate		
Finish	Brushed Stainless		
Insert Colour	White		
Gasket Colour	Transparent (Neoprene)		
Supplied Fixing Screw Finish	Polished Chrome		
Materials	Front Plate: Stainless Steel	Insert & Housing: Urea	
	Switch & Fuse Drawer Cover: Stainless Steel	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Switched	Yes		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Product Marking	Fused		
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

UK Design Registration: 3015621

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN