define®

Technical Specification

CLICK® Scolmore GROUP

Product Code: FPPN424

Description: 10AX 4 Gang 2 Way Toggle Plate Switch

Luckinslive 389091989





General Information

Dimensions (mm)	146 (W) x 86 (H) x 40 (D)
Plate Dimensions (mm)	146 (W) x 86 (H) x 1.3 (D)
Dimensions With Gasket (mm)	146 (W) x 86 (H) x 3 (D)
Plate Fixing Centres - Horizontal (mm)	120.6
Style	Flat Plate
Finish	Pearl Nickel
Gasket Colour	Transparent (Neoprene)
Supplied Fixing Screw Finish	Polished Chrome
Switch Finish	Pearl Nickel
Materials	Front Plate: Stainless Steel Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
	Switch Front & Nut: Cast Zinc Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	No
Operating Voltage (AC)	250
Frequency (Hz)	50
Inductive Load Rating (AX)	10
Load Rating Comments	Suitable for Fluorescent or Inductive Loads
Termination Type	Screw
Terminal Size (mm)	4.9 x 4.1
Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	4 x 1.5 or 2 x 2.5
Modular Rocker Switches	Yes
2 Way Switch	Yes
Minimum Back Box Depth (mm)	35
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125PN for pearl nickel finish.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN