define®

Technical Specification

CLiCK® Scolmore GROUP

Product Code: FPPN722WH

Description: 20A Ingot Double Pole Plate Switch

Luckinslive 389092221





General Information

Dimensions (mm)	86 (W) x 86 (H) x 28 (D)
Plate Dimensions (mm)	86 (W) x 86 (H) x 1.3 (D)
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 3 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Flat Plate
Finish	Pearl Nickel
Insert Colour	White
Gasket Colour	Transparent (Neoprene)
Supplied Fixing Screw Finish	Polished Chrome
Materials	Front Plate: Stainless Steel
	Switch Cover: Stainless Steel
	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass
	Insert & Housing: Urea
	Terminals: Brass
	Contacts: Silver "on-lay" Copper / Brass
	Earth Strap: Mild Steel
Anti Microbial Certified	No
Operating Voltage (AC)	250
Frequency (Hz)	50
Resistive Load Rating (A)	20
Termination Type	Screw
Terminal Size (mm)	Ø5
Terminal Torque Value (Nm)	1.8
Terminal Capacity - Solid (mm^2)	3 x 2.5
Double Pole Switch	Yes
Twin Earth Terminals	Yes
Minimum Back Box Depth (mm)	35
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN