define®

# Technical Specification


CLICK® Scolmore GROUP

Product Code: FPSS411WH

Luckinslive 389092962

Description: 10AX Ingot 1 Gang 2 Way Plate Switch





## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 86 (W) x 86 (H) x 25 (D) | | |
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 1.3 (D) | | |
| Dimensions With Gasket (mm) | 86 (W) x 86 (H) x 3 (D) | | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | | |
| MiniGrid Plate (Gang) | 1 | | |
| MiniGrid Single Width Module Quantity | 1 | | |
| MiniGrid Double Width Module Quantity | 0 | | |
| Style | Flat Plate | | |
| Finish | Stainless Steel | | |
| Insert Colour | White | | |
| Gasket Colour | Transparent (Neoprene) | | |
| Supplied Fixing Screw Finish | Polished Chrome | | |
| Materials | Front Plate: Stainless Steel | Insert: Urea | |
| | Switch Cover: Stainless Steel | Rear Housing: Nylon | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Contacts: Silver "on-lay" Copper / Brass | Internal Busbars: Formed Pressed Brass | |
| | Earth Strap: Mild Steel | | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Inductive Load Rating (AX) | 10 | | |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø3.5 | Terminal Torque Value (Nm) | 0.5 |
| Terminal Capacity - Solid ($mm^2$) | 4 x 1.5 or 2 x 2.5 | | |
| Modular Rocker Switches | Yes | | |
| 2 Way Switch | Yes | | |
| Minimum Back Box Depth (mm) | 25 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range. MINIGRID®

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN