define®

# Technical Specification

CLICK® Scolmore GROUP

Product Code: FPSS753BK

Luckinslive 389093411

Description: 13A Ingot Fused Connection Unit With Neon







## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 86 (W) x 86 (H) x 25 (D) | | |
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 1.3 (D) | | |
| Dimensions With Gasket (mm) | 86 (W) x 86 (H) x 3 (D) | | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | | |
| Style | Flat Plate | | |
| Finish | Stainless Steel | | |
| Insert Colour | Black | | |
| Gasket Colour | Transparent (Neoprene) | | |
| Supplied Fixing Screw Finish | Polished Chrome | | |
| Materials | Front Plate: Stainless Steel | Insert & Housing: Urea | |
| | Fuse Drawer Cover: Stainless Steel | Neon Lens: Polycarbonate | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Internal Busbars: Formed Pressed Brass | Earth Strap: Mild Steel | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 | | |
| Fuse Fitted Type | Plug Top Cartridge Fuse | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 or 2 x 4 | | |
| Switched | No | | |
| Twin Earth Terminals | Yes | | |
| Neon Indicator | Yes | Indicator Colour | Red |
| Product Marking | Fused | | |
| Minimum Back Box Depth (mm) | 35 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS 1363-4, BS 1362

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN