GRIDPRO

# Technical Specification

CLICK Scolmore GROUP

Product Code: GM2004BKBZ

Luckinslive 437084437

Description: 20AX 2 Way Retractive Switch Module





## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 24.5 (W) x 50 (H) x 22.5 (D) | | |
| Finish | Matt Bronze | | |
| Insert Colour | Black | | |
| Switch Finish | Matt Bronze | | |
| Materials | Body & Insert: Nylon | Switch: Urea | |
| | Switch Cover: Stainless Steel | Terminals: Brass | |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass | |
| | Spring: Spring Steel | | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Inductive Load Rating (AX) | 20 | | |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 1.2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 or 2 x 4 | | |
| 2 Way Switch | Yes | | |
| Retractive Contact Options | Press to Make or Break | | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN