GRIDPRO

# Technical Specification

CLICK Scolmore GROUP

Product Code: GM2028BK

Description: 20AX Intermediate Switch Module

Luckinslive 404476463







## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 24.5 (W) x 50 (H) x 22.5 (D) | | |
| Colour | Black | | |
| Insert Colour | Black | | |
| Switch Finish | Black | | |
| Materials | Body & Insert: Nylon | Switch: Urea | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Contacts: Silver "on-lay" Copper / Brass | | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Inductive Load Rating (AX) | 20 | | |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 1.2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 or 2 x 4 | | |
| Intermediate Switch | Yes | | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E:** sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN