GRIDPRO

Technical Specification

CLICK Scolmore GROUP

Product Code: GM2047BKAB

Description: 13A Fused Connection Module

Luckinslive 404477271





General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 25 (D)		
Finish	Antique Brass		
Insert Colour	Black		
Materials	Body & Insert: Nylon	Insert Cover: Stainless Steel	
	Internal Busbars: Brass	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated		
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5, 2 x 4		
Product Marking	Fused Symbol		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

CLIP-ON MODULES SCREW-IN MODULES

UK Patent: GB 2578427 , UK Design Registration: 3015621

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN