METALCLAD™ PRO RANGE

Technical Specification

Product Code: MCP012PW

Luckinslive 437625375

Description: 10AX 2 Gang 2 Way Plate Switch



General Information

Dimensions (mm)	88 (W) x 88 (H) x 48 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
MiniGrid Plate (Gang)	1
MiniGrid Single Width Module Quantity	2
MiniGrid Double Width Module Quantity	1
Style	Metal Clad Pro
Colour	Polar White
Insert Colour	Polar White
Supplied Fixing Screw Finish	Polished Chrome
Materials	Front Plate & Back Box: Electrophoretically Coated Steel Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Insert & Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Operating Voltage (AC)	250
Frequency (Hz)	50
Inductive Load Rating (AX)	10
Load Rating Comments	Suitable for Fluorescent or Inductive Loads
Termination Type	Screw
Terminal Size (mm)	Ø3.6
Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm^2)	4 x 1.5 or 2 x 2.5
Modular Rocker Switches	Yes
2 Way Switch	Yes
Supplied Back Box Depth (mm)	40
Back Box Knockouts - Total (mm)	6 x Ø20
Back Box Knockouts - Top (mm)	1 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Left Side (mm)	2 x Ø20
Back Box Knockouts - Right Side (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20
Back Box Earth Terminal Supplied	Yes
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS EN 60669-1, IEC 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH) MINIGRID®

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN