METALCLAD™ PRO RANGE

Technical Specification

Product Code: MCP1586RB

Description: 13A 2 Gang Switched Socket Outlet With Type A & C USB (4.2A) Outlets



General Information

Dimensions (mm)	148 (W) x 88 (H) x 48 (D)		
Style	Metal Clad Pro		
Colour	Dusty Grey		
Supplied Fixing Screw Finish	Polished Chrome		
Materials	Front Plate & Back Box: Electrophoretically Coated Steel		Insert & Rocker Switch: Urea
	Housing: Nylon		Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated		Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass		PCB: Mixed Components
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
USB Output Type	USB Type 'A' & Type 'C'		
USB Number Of Outputs	2	USB Charging Total Load (A)	4.2
USB Charging Voltage (V DC)	5	USB Standby Current (mA)	2
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Single Pole Switched	Yes		
3 Pin Safety Shuttered	Yes		
Twin Earth Terminals	Yes		
Switch Legend Design	Block		
Switch Legend Colour	Red		
Product Marking	DC, 5V 3A, 5V 2.4A max, 4.2A		
Supplied Back Box Depth (mm)	40		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20	Warranty - Electronics (Years)	2

Standards BS 1363-2, BS EN IEC 62368-1, BS EN 62680-1-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Independent Charging: 5V DC, 4.2A – USB Type A (2.4A), USB Type C (3A)
Dual Charging: 5V DC, 4.2A - USB Type A (1.2A), USB Type C (3A)

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN