METALCLAD™ PRO RANGE

Technical Specification

CLICK® Scolmore GROUP

Product Code: MCP536BK

Luckinslive 437624897

Description: 13A 2 Gang Double Pole Switched Socket Outlet



General Information

Dimensions (mm)	148 (W) x 88 (H) x 48 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Metal Clad Pro		
Colour	Black		
Insert Colour	Black		
Supplied Fixing Screw Finish	Matt Black		
Materials	Front Plate & Back Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea	
	Rear Housing: Urea	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
3 Pin Safety Shuttered	Yes		
Twin Earth Terminals	Yes		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	8 x Ø20		
Back Box Knockouts - Top (mm)	2 x Ø20	Back Box Knockouts - Bottom (mm)	3 x Ø20
Back Box Knockouts - Left Side (mm)	1 x Ø20	Back Box Knockouts - Right Side (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards

BS 1363-2

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN