MINIGRID®

Technical Specification

CLICK® Scolmore GROUP

Product Code: MD002PN

Luckinslive 389101620

Description: 10AX Ingot 2 Way Switch Module





General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)		
Finish	Pearl Nickel		
Materials	Rocker Switch: Urea	Rear Housing: Nylon	
	Switch Cover: Stainless Steel	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass		
Operating Voltage (AC)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	10		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm^2)	4 x 1.5 or 2 x 2.5		
Modular Rocker Switches	Yes		
2 Way Switch	Yes		
Minimum Back Box Depth (mm)	16 (25 Flat Plate)		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN