MINIGRID®

# Technical Specification

CLICK® Scolmore GROUP

Product Code: MD018BK-FF

Luckinslive 405856493

Description: 13A/10AX Double Pole Switch Module






## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 25 (W) x 53 (H) x 20 (D) | | |
| Colour | Black | | |
| Materials | Rocker Switch: Urea | Rear Housing: Nylon | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Contacts: Silver "on-lay" Copper / Brass | Internal Busbars: Formed Pressed Brass | |
| Anti Microbial Certified | Yes | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 | | |
| Inductive Load Rating (AX) | 10 | | |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø3.5 | Terminal Torque Value (Nm) | 0.5 |
| Terminal Capacity - Solid ($mm^2$) | 4 x 1.5 or 2 x 2.5 | | |
| Modular Rocker Switches | Yes | | |
| Double Pole Switch | Yes | | |
| Product Marking | Fridge Freezer | | |
| Minimum Back Box Depth (mm) | 16 (25 Flat Plate) | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN