MINIGRID®

Technical Specification

CLICK® Scolmore GROUP

Product Code: MD018PW-FF

Luckinslive 405855546

Description: 13A/10AX Double Pole Switch Module





General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)		
Colour	Polar White		
Materials	Rocker Switch: Urea	Rear Housing: Nylon	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Inductive Load Rating (AX)	10		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm^2)	4 x 1.5 or 2 x 2.5		
Modular Rocker Switches	Yes		
Double Pole Switch	Yes		
Product Marking	Fridge Freezer		
Minimum Back Box Depth (mm)	16 (25 Flat Plate)		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN