MINIGRID®

# Technical Specification

CLICK® Scolmore GROUP

Product Code: MD022PW-DW

Description: 20A Double Pole Switch Module

Luckinslive 405857379







## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 41 (W) x 52.5 (H) x 22 (D) | | |
| Colour | Polar White | | |
| Materials | Rocker Switch: Urea | Rear Housing: Nylon | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Contacts: Silver "on-lay" Copper / Brass | Internal Busbars: Formed Pressed Brass | |
| Anti Microbial Certified | Yes | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 20 | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø4.4 | Terminal Torque Value (Nm) | 1.2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 or 2 x 4 | | |
| Modular Rocker Switches | Yes | | |
| Double Pole Switch | Yes | | |
| Product Marking | Dishwasher | | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN