MINIGRID®

Technical Specification

CLiCK® Scolmore GROUP

Product Code: MD023PW-FD

Luckinslive 405859254

Description: 20A Double Pole Switch With Neon Module





General Information

Dimensions (mm)	41 (W) x 52.5 (H) x 22 (D)		
Colour	Polar White		
Materials	Rocker Switch: Urea	Rear Housing: Nylon	
	Neon Cover: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass		
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20		
Termination Type	Screw		
Terminal Size (mm)	Ø4.4	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Modular Rocker Switches	Yes		
Double Pole Switch	Yes		
Neon Indicator	Yes	Indicator Colour	Orange
Product Marking	Fridge		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN