Technical Specification

Product Code: MM030BK

Luckinslive 389104203

Description: 15A 110V US Socket Outlet Module





General Information

Dimensions (mm)	50 (W) x 50 (H) x 25.5 (D)		
Colour	Black		
Materials	Cover & Housing: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass	
Anti Microbial Certified	No		
Operating Voltage (AC)	125	Frequency (Hz)	
Resistive Load Rating (A)	15		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm^2)	3 x 2.5 or 2 x 4		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	2		

Standards UL 498

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
The US module requires a 125V 60Hz supply for use with US appliance plugs
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN