Technical Specification

Product Code: MM586BK

Luckinslive 435925666

Description: 2A Type A & 3A Type C USB Dual Charging Module



General Information

Dimensions (mm)	25 (W) x 55.7 (H) x 37 (D)		
Colour	Black		
Materials	Cover & Housing: Polycarbonate PCB: Electronic Components	Terminals& Screws: Brass	
Anti Microbial Certified	No		
Operating Voltage (AC)	100-240	Frequency (Hz)	50/60
Resistive Load Rating (A)	2 & 3		
USB Output Type	USB Type 'A' & Type 'C'		
USB Number Of Outputs	2	USB Charging Total Load (A)	5
USB Charging Voltage (V DC)	5	USB Standby Current (W)	0.075
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.4
Terminal Capacity - Solid (mm^2)	2 x 1.5		
Product Marking	5V 2A & 5V 3A		
Minimum Back Box Depth (mm)	35 (47 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	0 to +40		
Warranty (Years)	2		

Standards BS IEC 62368-1, BS EN 61000-6-1, BS EN 61000-6-3

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Internally fused which enables direct mains supply.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN