AquIP66®

Technical Specification

Product Code: OA2652AG

Luckinslive 437662781

Description: 13A Fused Connection DP Switched IP66 Weatherproof Unit With LED





General Information

Dimensions (mm)	87 (W) x 158 (H) x 90 (D)		
Accessory Fixing Centres (mm)	60.3		
Colour	Anthracite Grey		
Gasket Colour	Black		
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber	
	Accessory Plate & Housing: Urea	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
LED Indicator	Yes	Indicator Colour	Red
Product Marking	Fused		
Back Box Knockouts - Total (mm)	7 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	Back Box Knockouts - Sides (mm)	2 x Ø20
Ingress Protection	IP66		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 1363-4, BS 1362, BS EN 60529

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN