AquIP66®

Technical Specification

Product Code: OA411AGU

Luckinslive 408392129

Description: 10AX 1 Gang 2 Way IP66 Weatherproof Switch Unit



General Information

Dimensions (mm)	91 (W) x 106 (H) x 72.5 (D)		
Colour	Anthracite Grey		
Gasket Colour	Black		
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber	
	Switch Membrane: Neoprene	Switch: Urea	
	Rear Housing: Nylon	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass		
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	10		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm^2)	4 x 1.5 or 2 x 2.5		
Modular Rocker Switches	Yes		
2 Way Switch	Yes		
Back Box Knockouts - Total (mm)	5 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	Back Box Knockouts - Sides (mm)	1 x Ø20
Ingress Protection	IP66		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1, BS EN 60529

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with 13A/10AX modules in the MiniGrid Range. MINIGRID®

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN