AquIP66®

# Technical Specification

Product Code: OA412AGU

Luckinslive 408392239

Description: 10AX 2 Gang 2 Way IP66 Weatherproof Switch Unit



## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 91 (W) x 106 (H) x 72.5 (D) | | |
| Colour | Anthracite Grey | | |
| Gasket Colour | Black | | |
| Materials | Cover, Housing & Clip: Polycarbonate | Seal & Gasket: Rubber | |
| | Switch Membrane: Neoprene | Switch: Urea | |
| | Rear Housing: Nylon | Terminals: Brass | |
| | Terminal Screws: Steel & Yellow Passivated | Contacts: Silver "on-lay" Copper / Brass | |
| | Internal Busbars: Formed Pressed Brass | | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Inductive Load Rating (AX) | 10 | | |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø3.5 | Terminal Torque Value (Nm) | 0.5 |
| Terminal Capacity - Solid ($mm^2$) | 4 x 1.5 or 2 x 2.5 | | |
| Modular Rocker Switches | Yes | | |
| 2 Way Switch | Yes | | |
| Back Box Knockouts - Total (mm) | 5 x Ø20 | | |
| Back Box Knockouts - Top (mm) | 1 x Ø20 | Back Box Knockouts - Bottom (mm) | 1 x Ø20 |
| Back Box Knockouts - Rear (mm) | 1 x Ø20 | Back Box Knockouts - Sides (mm) | 1 x Ø20 |
| Ingress Protection | IP66 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS EN 60669-1, BS EN 60529

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with 13A/10AX modules in the MiniGrid Range. MINIGRID®

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN