AquIP66®

Technical Specification

CLICK® Scolmore GROUP

Product Code: OARCDP036 Luckinslive 433720478

Description: 13A 2 Gang IP66 Weatherproof Type A Passive RCD Switched Socket Outlet



General Information

Dimensions (mm)	158 (W) x 158 (H) x 90 (D)		
Accessory Fixing Centres (mm)	120.6		
Colour	Anthracite Grey		
Materials	Cover, Housing & Clip: Polycarbonate	Seal & Gasket: Rubber	
	Accessory Plate & Housing: Urea	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
	PCB: Mixed Components		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Breaking Capacity (A)	250 (Earth Leakage)		
Through Fault Withstand (A)	1500		
Trip Speed	Less than 40ms at 150mA Residual Current		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 3 x 4		
Switched	Yes		
Single Pole Switched	Yes		
Twin Earth Terminals	Yes		
Back Box Knockouts - Total (mm)	8 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm)	2 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	Back Box Knockouts - Sides (mm)	2 x Ø20
Ingress Protection	IP66		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20	Warranty - Electronics (Years)	2

Standards BS 1363-2, IEC 62640, BS 7288, BS EN 60529, IEC 61000-6-1 & IEC 61000-6-3

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN