essentials™

Technical Specification

Product Code: PA302

Luckinslive 389120009

Description: 13A Resilient Plug Top (3A Fused) Fast Grip



General Information

Dimensions (mm)	49.5 (W) x 21 (D) x 49.5 (H)		
Colour	White		
Materials	Body: Nylon	Pins: Brass	
	Internal Busbars: Formed Pressed Brass	Fuse: BS 1362 Approved	
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	3		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø3.1	Terminal Torque Value (Nm)	0.4
Terminal Capacity - Solid (mm^2)	1.5		
Product Marking	Fused		
Cable Entry Dimensions (mm)	Ø10.8		
Cable Restraint Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 1363/A, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Always refer to the circuit diagram supplied with the relevant product.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN