essentials™

# Technical Specification

Product Code: PA330

Luckinslive 389120083

Description: 13A Resilient Plug Top (13A Fused) Bar Grip



## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 49.5 (W) x 21 (D) x 49.5 (H) | | |
| Colour | Black | | |
| Materials | Body: Nylon | Pins: Brass | |
| | Internal Busbars: Formed Pressed Brass | Fuse: BS 1362 Approved | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 | | |
| Fuse Fitted Type | Plug Top Cartridge Fuse | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø3.1 | Terminal Torque Value (Nm) | 0.4 |
| Terminal Capacity - Solid ($mm^2$) | 1.5 | | |
| Product Marking | Fused | | |
| Cable Entry Dimensions (mm) | Ø10.8 | | |
| Cable Restraint Supplied | Yes | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 10 | | |

**Standards** BS 1363/A, BS 1362

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Always refer to the circuit diagram supplied with the relevant product.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN