essentials™

Technical Specification

Product Code: PRC038

Description: 6" T2 BC TRS Pendant Set

Luckinslive 394112604



General Information

Dimensions (mm)	86 (Dia) x 30		
Colour	Polar White		
Materials	Cover, Body & Skirt: Urea	Rear Plate: Polycarbonate	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Cable Type: 2G H05V2V2-F	Internal Housing: Reinforced Nylon	
	Springs: Spring Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	2		
Pre-wired Cable Specification	2G 0.75mm² H05V2V2-F		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm²)	2 x 1.5		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS EN 61184, BS 67

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Cable entry seal helps prevent moisture ingress.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN