essentials™

Technical Specification

Product Code: PRW211 Luckinslive 389107569

Description: 50A Double Pole Pull Cord Switch With Mechanical 'On/Off' & Neon



General Information

Dimensions (mm)	86 (W) x 86 (H) x 43 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Round		
Colour	Polar White		
Materials	Front Plate: Urea	Terminal Housing: Urea	
	Neon Lens: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel	Pull Bell: Urea	
Anti Microbial Certified	Yes (Urea Mouldings)		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	50		
Termination Type	Screw		
Twin Screw Terminals	Yes		
Terminal Size (mm)	Ø6.7	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm^2)	1 x 25		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Neon Indicator	Yes	Indicator Colour	Orange
Mechanical Indicator	Yes		
Mechanical Indicator Type	On/Off Rotating Legend		
Minimum Back Box Depth (mm)	47		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN