Technical Specification

Product Code: PRW215
Description: 45A 1 Gang Cooker Connection Plate

Luckinslive 389107585





General Information

Plate Dimensions (mm)	86 (W) x 86 (H) x 22.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Square Edge		
Colour	Polar White		
Supplied Fixing Screw Finish	Polished Chrome		
Materials	Front Plate: Urea	Earthing Yoke: Mild Steel	
	Terminal Housing: Urea	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated		
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	45		
Termination Type	Screw		
Terminal Size (mm)	Ø4.6	Terminal Torque Value (Nm)	0.8
Terminal Capacity - Solid (mm^2)	2 x 10		
Flex Outlet Available	Yes		
Flex Outlet Location	Bottom of Plate	Flex Outlet Dimension (mm)	20 x 21
Minimum Back Box Depth (mm)	35		
Cable Restraint Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	25		

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN