Technical Specification

Product Code: QOE8333BLK **Luckinslive** 438092703

Description: 3x3 Fast Fit 3 Way 32A IP68 (M16+M20) Connection Box (Lever Terminals)



Dimensions

Length (mm)	141
Width (mm)	88
Height (mm)	37
Minimum Cable Diameter (mm)	5
Maximum Cable Diameter (mm)	8
Conductor Strip Length (mm)	10

General Information

Colour	Black & Red
Rated Current (A)	32
Conductor Size Range (mm²)	0.2 - 4.0 Stranded or Solid Core
Tightening Torque (Nm)	2.5
Ingress Protection	IP68 (Tested to 1 Metre at 60 Minutes)
Working Temperature (°C)	60
Operational Temperature (°C)	-40 to +85
Warranty (Years)	1

Materials

Body Components: Polycarbonate
Membranes: Silica Gel
Levers: Polyamide 66
Terminals: Tinned Copper

Additional Information

2 x M20 inline entries and 1 x M16 entry with seals and membranes. 4 fixing points.
Supplied with 3x3 port lever terminals.

Standards

BS 6220
BS EN 60670
BS EN 60529:1992+A2:2013 (Sections 13 & 14)
BS EN 60998-1: 2004
BS EN 60998-2-2:2004

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 300600 | **F:** +44 (0)1827 300620
E: sales@unicrimp.com | **W:** unicrimp.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN