definity™ COMPLETE

Technical Specification


CLICK® Scolmore GROUP

Product Code: SFBK025BK

Luckinslive 435279752

Description: 10AX 1 Gang Intermediate Plate Switch





General Information

Dimensions (mm)	86 (W) x 86 (H) x 25 (D)
Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
MiniGrid Plate (Gang)	1
MiniGrid Single Width Module Quantity	1
MiniGrid Double Width Module Quantity	0
Style	Screwless Complete
Finish	Matt Black
Insert Colour	Black
Compatible Cover Plate	SCP401#
Materials	Cover Plate: Polycarbonate Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
	Insert: Polycarbonate Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel
Anti Microbial Certified	No
Operating Voltage (AC)	250
Frequency (Hz)	50
Inductive Load Rating (AX)	10
Load Rating Comments	Suitable for Fluorescent or Inductive Loads
Termination Type	Screw
Terminal Size (mm)	Ø3.5
Terminal Torque Value (Nm)	0.5
Terminal Capacity - Solid (mm^2)	4 x 1.5 or 2 x 2.5
Intermediate Switch	Yes
Minimum Back Box Depth (mm)	25
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
The MiniGrid module installed is moulded black (BK) finish.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with moulded black (BK) modules in the MiniGrid Range. MINIGRID®

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN